



## EC declaration of conformity

For the following equipment:

Product Name: Switching Power Supplies

Model Designation:

PCD/PLD-40-xB(x=350,500,700,1050,1400,1750)

PCD/PLD-60-xB(x=500,700,1050,1400,1750,2000,2400)

PCD-60-1500BGAM

is herewith confirmed to comply with the requirements set out in the Council Directive, the following standards were applied:

## RoHS Directive (2011/65/EC)

Energy-Related Products Directive (2009/125/EC) Implementing measure COMMISSION REGULATION(EC) No 1194/2012

Low Voltage Directive (2006/95/EC):

EN61347-1:2008+A1:2011/EN61347-2-13:2006/ EN 62384:2006+A1:2009 ENEC certificate No: NO3347

Electromagnetic Compatibility Directive (2004/108/EC):

EMI (Electro-Magnetic Interference)

Conducted emission / Radiated emission

| EN5501 | 5:2006+A1:2007+A2:2009 |
|--------|------------------------|
|        |                        |

|                                   | · Class | C (>7E9/ Lood)   |
|-----------------------------------|---------|------------------|
| EN61000-3-2: 2006+A1:2009+A2:2009 | Clas    | ss C (≥75% Load) |

EN61000-3-3: 2008 Voltage flicker

EMS (Electro-Magnetic Susceptibility)

| FN61   | E 4 | 7.01 | $\alpha \alpha \alpha$ |
|--------|-----|------|------------------------|
| HIMD I | 24  | 1 /  | 11 159                 |

Harmonic current

| EN61547:2009             |                      |                   |              |                    |     |
|--------------------------|----------------------|-------------------|--------------|--------------------|-----|
| ESD air                  | IEC 61000-4-2:2008   | -                 | Level 3      | 8KV                |     |
| ESD contact              | IEC 61000-4-2:2008   |                   | Level 2      | 4KV                |     |
| RF field susceptibility  | IEC 61000-4-3:2010   |                   | Level 2      | 3V/m               |     |
| EFT bursts               | IEC 61000-4-4:2004+  | A1:2010           | Level 2      | 1KV/5KHz           |     |
| Surge susceptibility     | IEC 61000-4-5:2005   |                   | Level 4      | 2KV/Line-Line      |     |
| Conducted susceptibility | IEC 61000-4-6:2008   |                   | Level 2      | 3V                 |     |
| Magnetic field immunity  | IEC 61000-4-8:2009   |                   | Level 2      | 3A/m               | 116 |
| Voltage din interruption | IFC 61000-4-11: 2004 | 30% dip 10periods | 100% interru | otions 0.5 periods |     |

/oltage dip, interruption

Component power supply will be operated with a final equipment. Since EMC performance will be affected by the complete installation, the final equipment manufacturers must re-qualify EMC Directive on the complete installation again.

Tests above are only to be performed with LED load.

For guidance on how to perform these EMC tests, please refer to TDF (Technical Documentation File).

To fulfill requirements of the latest ErP regulation for lighting fixtures, this LED power supply can only be used behind a switch without permanently connected to the mains

This Declaration is effective from serial number HB4xxxxxxx

Person responsible for marking this declaration:

Mean Well (Guangzhou) Electronics Co., Ltd.

(Manufacturer Name)

2/F, A Building, Yuean Ind. Park, Huangcun, Dongpu Town, Tianhe District, Guangzhou, China

(Manufacturer Address)

Howay\_Lin/Engineering Manager:

(Name / Position)

July. 1st. 2014

Frank Peng/RD Manager:

(Name / Position)

GuangZhou

(Date)

(Place)