



Test Report: HBG-240-60

240W Single Output Switching Power Supply

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Component Stress Test

■ SAFETY & E.M.C. TEST

Safety Test

E.M.C. Test

■ RELIABILITY TEST

ENVIRONMENT TEST

■ DESIGN VERIFY TEST

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1 : 350 mVp-p (Max)	I/P : 230VAC O/P : FULL LOAD Ta : 25°C	V1 : 150 mVp-p (Max)	P
2	CONSTANT CURRENT REGION	CH1: 36 V ~ 60 V	I/P : 230VAC O/P : CV MODE Ta : 25°C	O/P= 36V : 4.033 A O/P= 60V : 4.035 A	P
3	CURRENT ADJUST RANGE	CH1: 2.4A ~ 4.0 A	I/P : 230VAC I/P : 115VAC O/P : CV MODE Ta : 25°C	1.515 A ~ 4.238 A /230VAC 1.517 A ~ 4.237 A /115VAC	P
4	OUTPUT VOLTAGE TOLERANCE	V1 : 1%~ -1% (Max)	I/P : 100 VAC / 305 VAC O/P : FULL/ MIN LOAD Ta : 25°C	V1 : 0.520 %~ -0.051 %	P
5	LINE REGULATION	V1 : 0.5%~ -0.5% (Max)	I/P : 100 VAC ~ 305 VAC O/P : FULL LOAD Ta : 25°C	V1 : 0 %~ 0 %	P
6	LOAD REGULATION	V1 : 0.5%~ -0.5% (Max)	I/P : 230 VAC O/P : FULL ~MIN LOAD Ta : 25°C	V1 : 0.042 %~ -0.051 %	P
7	SET UP TIME	230VAC : 2500 ms (Max) 115VAC : 2500 ms(Max)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 1481 ms 115VAC/ 1477 ms	P
8	RISE TIME	230VAC : 120 ms (Max) 115VAC : 120 ms (Max)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 38.90 ms 115VAC/ 39.44 ms	P
9	HOLD UP TIME	230VAC : 15 ms (TYP) 115VAC : 15 ms (TYP)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 33.00 ms 115VAC/ 32.98 ms	P
10	OVER/UNDERSHOOT TEST	< ±5%	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	TEST : <5 %	P
11	DYNAMIC LOAD	V1 : 6000 mVp-p	I/P : 230 VAC (1).O/P : FULL /Min LOAD 90%DUTY/ 1KHZ (2).O/P : FULL /Min LOAD 50%DUTY/ 120HZ Ta : 25°C	(1) 368 mVp-p (2) 3760 mVp-p	P

12	DIMMER TEST	SPEC:										
		*Output constant current level can be adjusted through output cable by 1 ~ 10Vdc, PWM signal or resistor between ADJ1(+) and ADJ2(-).										
		*Reference resistance value for output current adjustment (Typical)										
		Resistance value	10K	20K	30K	40K	50K	60K	70K	80K	90K	100K
		Output current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%
		*1 ~ 10V dimming function for output current adjustment (Typical)										
		Dimming value	1V	2V	3V	4V	5V	6V	7V	8V	9V	10V
		Output current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%
		*10V PWM signal for output current adjustment (Typical)										
		Duty value	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%
		Output current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%
		TEST RESULT: I/P : 230 VAC ;Ta : 25°C										
1	Resistance value	10K	20K	30K	40K	50K	60K	70K	80K	90K	100K	
	Output current	0.266A	0.717A	1.164A	1.595A	2.028A	2.458A	2.895A	3.328A	3.755A	4.015A	
	%	6.65%	17.93%	29.10%	39.88%	50.70%	61.45%	72.38%	83.20%	93.88%	100.4%	
2	Dimming value	1V	2V	3V	4V	5V	6V	7V	8V	9V	10V	
	Output current	0.243A	0.676A	1.109A	1.524A	1.929A	2.347A	2.803A	3.239A	3.672A	4.039A	
	%	6.08%	16.90%	27.73%	38.10%	48.23%	58.68%	70.08%	80.98%	91.80%	101.0%	
3	Duty value	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	
	Output current	0.278A	0.700A	1.126A	1.532A	1.941A	2.358A	2.777A	3.202A	3.622A	4.010A	
	%	6.95%	17.5%	28.15%	38.30%	48.53%	58.95%	69.43%	80.05%	90.55%	100.3%	

P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	100VAC~305 VAC	I/P : TESTING O/P : FULL LOAD Ta : 25°C	87 V~305V	P
			I/P : LOW-LINE-3V=97 V HIGH-LINE=305 V O/P : FULL/MIN LOAD ON : 30 Sec . OFF : 30 Sec 10MIN (AC POWER ON/OFF NO DAMAGE)	TEST : OK	
2	INPUT FREQUENCY RANGE	47HZ ~63 HZ NO DAMAGE OSC	I/P : 100 VAC ~ 305 VAC O/P : FULL-MIN LOAD Ta : 25°C	TEST : OK	P
3	POWER FACTOR	0.95 / 230 VAC(TYP) 0.98 / 115 VAC(TYP) 0.93 / 277 VAC(TYP)	I/P : 230 VAC I/P : 115 VAC I/P : 277 VAC O/P : FULL LOAD Ta : 25°C	PF= 0.970 / 100% PF= 0.995 / 100% PF= 0.940 / 100%	P
4	EFFICIENCY	93.5% (TYP)	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	93.89 %	P
5	INPUT CURRENT	230V/ 1.3 A (TYP) 115V/ 2.5 A (TYP) 277V/ 1.2 A (TYP)	I/P : 230 VAC I/P : 115 VAC I/P : 277 VAC O/P : FULL LOAD Ta : 25°C	I= 1.140 A/ 230 VAC I= 2.315 A/ 115 VAC I= 0.968 A/ 277 VAC	P
6	INRUSH CURRENT	230V/ 75 A (TYP) COLD START	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	I= 56.81 A/ 230 VAC	P
7	LEAKAGE CURRENT	< 0.75 mA / 277 VAC	I/P : 277 VAC O/P : Min LOAD Ta : 25°C	L-CASE : 0.3953 mA N-CASE : 0.3900 mA	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	95 % ~ 108 %	I/P : 230 VAC I/P : 115 VAC O/P : TESTING Ta : 25°C	100.88 %/ 230 VAC 100.78 %/ 115 VAC Constant current limiting ,recovers automatically after fault condition is removed	P
2	OVER VOLTAGE PROTECTION	CH1 : 62 V ~ 82 V	I/P : 230 VAC I/P : 115 VAC O/P : MIN LOAD Ta : 25°C	66.6 V/ 230 VAC 66.6 V/ 115 VAC Shut down o/p voltage, re-power on to recover	P
3	OVER TEMPERATURE PROTECTION	SPEC : TSW1 : 95± 5°C O.T.P. NO DAMAGE	I/P : 230 VAC O/P : FULL LOAD	O.T.P. Active Shut down o/p voltage, recovers automatically after temperature goes down	P
4	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P : 305 VAC O/P : FULL LOAD Ta : 25°C	NO DAMAGE Hiccup mode, recovers automatically after fault condition is removed.	P

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor (D to S) or (C to E) Peak Voltage	Q6 Rated : STF26NM60N: 600V/20A	I/P : High-Line +3V = 308 V O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue Ta : 25°C	(1) 462 V (2) 460 V (3) 452 V	P
2	Diode Peak Voltage	Q101 Rated : V30200C: 200 V/ 30 A	I/P : High-Line +3V = 308 V O/P : (1)Full Load Turn on (2)Output Short (3)Full load continue Ta : 25°C	(1) 142 V (2) 19.3 V (3) 136 V	P
3	Input Capacitor Voltage	C5 Rated : 150u/450V 105°C 18*45 CST	I/P : High-Line +3V = 308 V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25°C	(1) 446 V (2) 444 V (3) 444 V	P
4	Control IC Voltage Test	U70 Rated : L6599ATD: 16V (MAX)	I/P : High-Line +3V = 308 V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25°C	(1) 14.9 V (2) 14.9 V (3) 14.9 V	P
5	Power Transistor (D to S) or (C to E) Peak Voltage	Q1 Rated : IPW60R190C6 :650V/20.2A	I/P : High-Line +3V = 308 V O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue Ta : 25°C	(1) 556 V (2) 500 V (3) 502 V	P

■ SAFETY & E.M.C. TEST

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P : 3.75 KVAC/min I/P-FG : 1.88 KVAC/min O/P-FG : 0.5 KVAC/min	I/P-O/P : 4 KVAC/min I/P-FG : 2.26 KVAC/min O/P-FG : 0.6 KVAC/min Ta : 25°C	I/P-O/P : 3.081 mA I/P-FG : 3.372 mA O/P-FG : 1.856 mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P : 500VDC>100MΩ I/P-FG : 500VDC>100MΩ O/P-FG : 500VDC>100MΩ	I/P-O/P : 500 VDC I/P-FG : 500 VDC O/P-FG : 500 VDC Ta : 25°C /70%RH	I/P-O/P : >9999 MΩ I/P-FG : >9999 MΩ O/P-FG : >9999 MΩ NO DAMAGE	P
3	GROUNDING CONTINUITY	FG(PE) TO CHASSIS OR TRACE < 100 mΩ	40 A / 2min Ta : 25°C / 70%RH	17 mΩ	P

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	HARMONIC	EN61000-3-2 CLASS C	I/P:220VAC/230VAC/240VAC50HZ O/P:100%,75%,60%LOAD Ta:25°C	PASS	P
2	CONDUCTION	EN55015	I/P: 230 VAC (50HZ)/115V[60HZ] O/P:FULL/65% LOAD Ta:25°C	PASS Test by certified Lab	P
3	RADIATION	EN55015	I/P: 230 VAC (50HZ)/115V[60HZ] O/P: FULL/65% LOAD Ta:25°C	PASS Test by certified Lab	P
4	E.S.D	EN61000-4-2 LIGHT INDUSTRY AIR:8KV / Contact:4KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
5	E.F.T	EN61000-4-4 LIGHT INDUSTRY INPUT: 1KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
6	SURGE	IEC61000-4-5 INDUSTRY L-N :2KV L,N-PE:4KKV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
7	Test by certified Lab & Test Report Prepare				

■ **RELIABILITY TEST**

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT																																																																																																																			
1	TEMPERATURE RISE TEST	MODEL : HBG-240-60 1. ROOM AMBIENT BURN-IN : 2.5 HRS I/P : 230VAC O/P : 95% LOAD Ta=31.9 °C 2. HIGH AMBIENT BURN-IN : 3.5 HRS I/P : 230VAC O/P : 95% LOAD Ta=60.0 °C			P																																																																																																																			
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>P/N</th> <th>ROOM AMBIENT Ta= 31.9 °C</th> <th>HIGH AMBIENT Ta= 60.0 °C</th> </tr> </thead> <tbody> <tr><td>1</td><td>LF1</td><td>TR-953</td><td>55.2°C</td><td>83.7°C</td></tr> <tr><td>2</td><td>LF2</td><td>TR915-R2</td><td>58.4°C</td><td>86.3°C</td></tr> <tr><td>3</td><td>BD1</td><td>US10KB80R</td><td>60.4°C</td><td>88.8°C</td></tr> <tr><td>4</td><td>C5</td><td>150u/450V 18*45 CST</td><td>58.3°C</td><td>85.8°C</td></tr> <tr><td>5</td><td>L2</td><td>TR-930</td><td>56.1°C</td><td>84.9°C</td></tr> <tr><td>6</td><td>C11</td><td>C/MPE 105/450V</td><td>59.0°C</td><td>86.3°C</td></tr> <tr><td>7</td><td>D3</td><td>1N5406</td><td>57.6°C</td><td>85.1°C</td></tr> <tr><td>8</td><td>D2</td><td>BYT79X-600</td><td>62.2°C</td><td>90.1°C</td></tr> <tr><td>9</td><td>L1</td><td>TF-6537</td><td>59.2°C</td><td>87.4°C</td></tr> <tr><td>10</td><td>Q1</td><td>IPW60R190C6</td><td>62.6°C</td><td>90.6°C</td></tr> <tr><td>11</td><td>U1</td><td>NCP1605DR2G</td><td>56.5°C</td><td>85.5°C</td></tr> <tr><td>12</td><td>C39</td><td>C/E 47u/25V 5*11 LE</td><td>56.1°C</td><td>84.7°C</td></tr> <tr><td>13</td><td>U70</td><td>L6599ATD</td><td>49.4°C</td><td>77.8°C</td></tr> <tr><td>14</td><td>Q3</td><td>STF26NM60N</td><td>63.1°C</td><td>91.3°C</td></tr> <tr><td>15</td><td>Q4</td><td>STF26NM60N</td><td>64.3°C</td><td>92.7°C</td></tr> <tr><td>16</td><td>T1</td><td>TF-6475</td><td>68.5°C</td><td>96.9°C</td></tr> <tr><td>17</td><td>Q101</td><td>V30200C</td><td>61.8°C</td><td>89.3°C</td></tr> <tr><td>18</td><td>Q102</td><td>V30200C</td><td>62.3°C</td><td>89.7°C</td></tr> <tr><td>19</td><td>C102</td><td>C/E 220uF/80V 10*23 ZLH</td><td>58.0°C</td><td>85.1°C</td></tr> <tr><td>20</td><td>C103</td><td>C/E 220uF/80V 10*23 ZLH</td><td>56.7°C</td><td>84.9°C</td></tr> <tr><td>21</td><td>C106</td><td>C/E 220uF/80V 10*23 ZLH</td><td>51.7°C</td><td>79.1°C</td></tr> <tr><td>22</td><td>LF100</td><td>TR950-R4</td><td>55.3°C</td><td>83.1°C</td></tr> </tbody> </table>	NO	Position		P/N	ROOM AMBIENT Ta= 31.9 °C	HIGH AMBIENT Ta= 60.0 °C	1	LF1	TR-953	55.2°C	83.7°C	2	LF2	TR915-R2	58.4°C	86.3°C	3	BD1	US10KB80R	60.4°C	88.8°C	4	C5	150u/450V 18*45 CST	58.3°C	85.8°C	5	L2	TR-930	56.1°C	84.9°C	6	C11	C/MPE 105/450V	59.0°C	86.3°C	7	D3	1N5406	57.6°C	85.1°C	8	D2	BYT79X-600	62.2°C	90.1°C	9	L1	TF-6537	59.2°C	87.4°C	10	Q1	IPW60R190C6	62.6°C	90.6°C	11	U1	NCP1605DR2G	56.5°C	85.5°C	12	C39	C/E 47u/25V 5*11 LE	56.1°C	84.7°C	13	U70	L6599ATD	49.4°C	77.8°C	14	Q3	STF26NM60N	63.1°C	91.3°C	15	Q4	STF26NM60N	64.3°C	92.7°C	16	T1	TF-6475	68.5°C	96.9°C	17	Q101	V30200C	61.8°C	89.3°C	18	Q102	V30200C	62.3°C	89.7°C	19	C102	C/E 220uF/80V 10*23 ZLH	58.0°C	85.1°C	20	C103	C/E 220uF/80V 10*23 ZLH	56.7°C	84.9°C	21	C106	C/E 220uF/80V 10*23 ZLH	51.7°C	79.1°C	22	LF100	TR950-R4	55.3°C	83.1°C		
NO	Position	P/N	ROOM AMBIENT Ta= 31.9 °C	HIGH AMBIENT Ta= 60.0 °C																																																																																																																				
1	LF1	TR-953	55.2°C	83.7°C																																																																																																																				
2	LF2	TR915-R2	58.4°C	86.3°C																																																																																																																				
3	BD1	US10KB80R	60.4°C	88.8°C																																																																																																																				
4	C5	150u/450V 18*45 CST	58.3°C	85.8°C																																																																																																																				
5	L2	TR-930	56.1°C	84.9°C																																																																																																																				
6	C11	C/MPE 105/450V	59.0°C	86.3°C																																																																																																																				
7	D3	1N5406	57.6°C	85.1°C																																																																																																																				
8	D2	BYT79X-600	62.2°C	90.1°C																																																																																																																				
9	L1	TF-6537	59.2°C	87.4°C																																																																																																																				
10	Q1	IPW60R190C6	62.6°C	90.6°C																																																																																																																				
11	U1	NCP1605DR2G	56.5°C	85.5°C																																																																																																																				
12	C39	C/E 47u/25V 5*11 LE	56.1°C	84.7°C																																																																																																																				
13	U70	L6599ATD	49.4°C	77.8°C																																																																																																																				
14	Q3	STF26NM60N	63.1°C	91.3°C																																																																																																																				
15	Q4	STF26NM60N	64.3°C	92.7°C																																																																																																																				
16	T1	TF-6475	68.5°C	96.9°C																																																																																																																				
17	Q101	V30200C	61.8°C	89.3°C																																																																																																																				
18	Q102	V30200C	62.3°C	89.7°C																																																																																																																				
19	C102	C/E 220uF/80V 10*23 ZLH	58.0°C	85.1°C																																																																																																																				
20	C103	C/E 220uF/80V 10*23 ZLH	56.7°C	84.9°C																																																																																																																				
21	C106	C/E 220uF/80V 10*23 ZLH	51.7°C	79.1°C																																																																																																																				
22	LF100	TR950-R4	55.3°C	83.1°C																																																																																																																				
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P : 305VAC/100VAC O/P : 95 % LOAD Ta= -40°C	TEST : OK	P																																																																																																																			
3	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 50 °C NO DAMAGE	I/P : 305 VAC O/P : 95% LOAD Ta= 60 °C HUMIDITY= 95 %R.H	TEST : OK	P																																																																																																																			
4	TEMPERATURE COEFFICIENT	± 0.03 %(0~50°C)	I/P : 230 VAC O/P : 95% LOAD	± 0.015 %(0~50°C)	P																																																																																																																			
5	STORAGE TEMPERATURE TEST	1. Thermal shock Temperature : -45°C~ +85°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 5 CYCLE 5. Input/Output condition : STATIC		OK	P																																																																																																																			

6	THERMAL SHOCK TEST	1. Thermal shock Temperature : -45°C~ +65°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 10 CYCLE 5. Input/Output condition : 230VAC/Full Load AC ON/OFF TEST turn on 58sec ; turn off 2sec	OK	P
7	VIBRATION TEST	1 Carton & 1 Set (1) Waveform : Sine Wave (2) Frequency : 10~500Hz (3) Sweep Time : 12min/sweep cycle (4) Acceleration : 5G (5) Test Time : 72min in each axis (X.Y.Z) (6) Ta : 25°C	TEST : OK	P
8	CAPACITOR LIFE CYCLE	HBG-240-60:SUPPOSE C102 IS THE MOST CRITICAL COMPONENT (1) I/P : 230VAC O/P : FULL LOAD Ta=25 °C LIFE TIME (2) I/P : 230VAC O/P : FULL LOAD Ta=60 °C LIFE TIME (3) I/P : 230VAC O/P : 75% LOAD Ta=60 °C LIFE TIME	(1) 511319.7 HRS (2) 48791.3 HRS (3) 61818.7 HRS	P
9	MTBF	MIL-HDBK-217F NOTICES2 PARTS COUNT TOTAL FAILURE RATE : 190.7KHRS		P
10	DMTBF/Accelerated Life Test	Demonstration Mean Time Between Failure(Expected Life) : 50,000 hours @ Tcase 70°C		P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2013/02/26	PRODUCT SAMPLE	PASS	ZOULF	HOWAY

2009/08/04 A50-G058